

Product Comparison Table

Flush Mount

- . Save installation space.
- . Install no screws.
- . Replace easy removal.



C4

E4

H4

X6

ITEM	020101	020202	020302	021101
LED Power	4PCS 3W LED	4PCS 3W LED	4PCS 3W LED	6PCS 3W LED
LED Lifespan	100000	100000	100000	100000
Flash settings	1-4HZ	1-4HZ	1-4HZ	1-4HZ
LENS	Reflex	TIR	TIR	TIR
Voltage	DC 10-30V	DC 10-30V	DC 10-30V	DC 10-30V
Max Power	9W	9W	9W	18W
Colour Available	Amber, Blue, Green, Red and White combination color	Amber, Blue, Red, White and combination color.	Blue, amber,Red,White,Green,pink and combination color	Amber, Blue, Red, White and combination color.
Ambient temperature	-20--+65°C	-20--+65°C	-20--+65°C	-20--+80°C
Waterproof	IP68	IP68	IP68	IP67
Product Dimension	4.5"L x 1.2"D x 1.1"H	5.8"L x 1.0"D x 1.8"H	4.7 "L x 1.7" W x 1.0"H	3.5"L x0.79"W x 0.7"H
Flash patterns	19	19	19	19
Housing Materials	Aluminum alloy Housing	Aluminum alloy Housing	Aluminum alloy Housing	Aluminum alloy Housing
Mounting	Surface mount	Surface mount	Surface mount	Surface mount;Bracket mount
Meet and Exceeds	ECE R65, ECE R10, SAE	ECE R65, ECE R10, SAE	ECE R65, ECE R10	ECE R65, SAE
Wire	20 AWG	20 AWG	20 AWG	20 AWG
Warranty	2 Years	2 Years	2 Years	2 Years
Listing Date	2012	2008	2011	2014