


Product Comparison Table

Surface mount

- . Solid and easy to install.
- . Used two screws.
- . Replace easy removal.



	E3	H3	F3	E24
ITEM	020201	020301	021201	021201
LED Power	3PCS 3W LED	3PCS 3W LED	3PCS 3W LED	24PCS 0.2W LED
LED Lifespan	100,000H	100,000H	100,000H	100,000H
Flash settings	1-4HZ	1-4HZ	1-4HZ	1-4HZ
LENS	TIR	TIR	TIR	/
Voltage	DC 10-30V	DC 10-30V	DC 10-30V	DC 10-30V
Max Power	7W	6W	5W	5W
Colour Available	red, blue , amber,white	Blue,amber ,Red,White	Blue,amber ,Red,White	Blue,amber ,Red,White
Ambient temperature	-20℃-- +65℃	-20℃-- +65℃	-20℃-- +65℃	-20℃-- +65℃
Waterproof	IP65	IP68	IP67	IP68
Product Dimension	4.6"L x 1.0"D x 1.8"H	4.0 "L x 1.7" W x 1.0"H	2.5 "L x 1.3" W x 0.5"H	4.6"L x 1.0"D x 1.8"H
Flash patterns	19	19	13	19
Housing Materials	Aluminum alloy Housing	Aluminum alloy Housing	Aluminum alloy Housing	Aluminum alloy Housing
Mounting	Surface mount	Surface mount	3m adhesive mount / Surface mount	Surface mount
Meet and Exceeds	ECE R10	ECE R10	SAE-10-W-2	/
Wire	20 AWG	20 AWG	22 AWG	20 AWG
Warranty	2 years	2 years	2 years	2 years
Listing Date	2008	2011	2014	2008