

www.911signal.com

Features

- > SAE J595 Class 1 and CA T13 certified
- > 10-33V multi-voltage input
- > Universal fit for all vehicles (sedan, SUV, pick-up truck etc) with a 12"x 6" license tag
- > Water-proof connector provided for easy installation
- > LED modules available in single, split, and dual colors with a steady-burn function
- > Maximum 180° visibility horizontally and 120° vertically
- > Provides full protection to the license tag without obstructing the information on it.
- > Frame made from ABS, UV, heat, water and corrosion resistant
- > Full encapsulated LED modules with moisture, vibration and corrosion resistance
- > Operating temperature: -30 to 70°C
- > 5 year warranty

Flash Patterns

Single Color

- Bandom (Default)
- Single (Split)
- 03 Double (Split)
- Quad (Split) 05 Quint (Split)
- 06 Ultra (Split)
- Single-Quad (Split)


- Single-H/L (Split)
- ECE R65 Single (All) ECE R65 Double (All)

- III Single (All)
- Double (All)
- Quad (All) Quint (All)
- Ultra (All)
- 16 Single-Quad (All)
- Single-H/L (All)
- III Steady 2 (California)
- III Steady 4 (All)

Dual Color

- Steady 2 (All)
- Steady 4 (All)
- Random (Default) ECE R65 single (All)
- ECE R65 double (All)
- G Single (All)
- 07 Double (All) Quad (All)
- Quint (All)
- Ultra (All) III Signle-Quad (All)
- Single-H/L (All)

Dimensions



Wiring



Single Color

- RED On/Off
- . BLACK GND YELLOW - Mode/Reset
- WHITE Alternation





- RED Color 2 "+" BLACK - GND
- · YELLOW Mode/Reset
- · WHITE Alternation

Color Sheet of Wire and LED

Combinations Wire	Opt.1	Opt.2	Opt.3	Opt.4	Opt.5	Opt.6
Blue	0	0	0	•	•	•
Red	•	•	0	•	0	0

Specifications

- . Mounting: Surface Mount
- · Max Power: 36W
- · Voltage: 10-33V
- · Flash Patterns:
- 19 (single color) / 12 (dual color)
- . LED: 24LEDs for each color





Avoid direct look into the light



